



CROSSBRACE DIAGRAM

NOTES:

1. THE LENGTHS DISPLAYED IN THE LENGTH COLUMN ARE DENOTED AS AxB (BAY LENGTH x LOCK SPAN)
2. ALL ALTERNATIVE UNITS ARE MILLIMETERS
3. THESE CROSS BRACES CAN BE USED FOR BOTH STANDARD AND ARCHED SCAFFOLDING TOWERS

| ITEM NO. | LENGTH "L" (AxB) | WEIGHT | COMPONENTS | |
|-----------|----------------------|----------|------------|------------------------|
| | | | S.NO. | DESCRIPTION |
| 02CB0624G | 60"x24" [1524x610] | 3.26 kgs | | |
| 02CB0630G | 60"x30" [1524x762] | 3.39 kgs | 1 | HINGE |
| 02CB0648G | 60"x48" [1524x1219] | 4.39 kgs | 2 | BRACE |
| 02CB0824G | 84"x24" [2134x610] | 4.39 kgs | 3 | FRAME CONNECTION Ø15mm |
| 02CB0830G | 84"x30" [2134x762] | 4.46 kgs | | |
| 02CB0848G | 84"x48" [2134x1219] | 4.80 kgs | | |
| 02CB1224G | 120"x24" [3048x610] | 6.09 kgs | | |
| 02CB1248G | 120"x48" [3048x1219] | 6.43 kgs | | |